HL-5450DN





Professional MonochromeLaser Printer Series

The HL-5450DN delivers high speed printing with network connectivity.

- Professional Monochrome Laser Series
- High-speed output at up to 38ppm
- 2-Sided (duplex) printing with booklet feature
- Network capability
- 1,200 x 1,200dpi resolution
- First page out in less than 8.5 seconds
- Up to 8,000[^] page high-yield toner cartridges

[^] In accordance to ISO/IEC 19752

HL-5450DN

Increase efficiency and productivity with up to 38 pages per minute printing. The quick print speeds ensure jobs are complete in an instant; freeing up time to grow your business and meet crucial deadlines.

Print your documents anywhere via different types of connectivity like Ethernet, mobile print, Air Print and Google Cloud Print.

Save when printing in bulk with the choice of standard and high yield toners of approximately 8,000* pages.

Reduce your electricity bills with the low power consumption of 0.6 watts in sleep mode when the printer is not in use.

*In accordance to ISO/IEC 19752

General

Technology Standard Print Speed (A4) 2-Sided Print Speed (Duplex) Warm Up Time First Print Out Time

Resolution Processor Memory Capacity

Local Interface Network Interface Print Languages LED Display Mobile Printing

Electrophotographic laser printe Up to 38ppm (pages per minute) Up to 18ipm (images per minute) Less than 1 second (from sleep mode) Less than 8.5 seconds (from ready mode) 1,200 x 1,200dpi, HQ1200 (2,400 x 600dpi quality), 600 x 600dpi

64MB (expandable up to 320MB using 1 x 144 pin, 16bit DDR2 DIMM) Hi-Speed USB2.0

Ethernet (10Base-T/100Base-TX)

PCL6, BR-Script3 (Postscript®3~ Language Emulation), IBM Proprinter XL & Epson FX-850 Toner LED, drum LED, paper LED, back cover LED

iPrint&Scan, Google Cloud Print, Air Print



Paper Handling

Paper Input

250 sheet standard paper tray 50 sheet multi-purpose trav

500 sheet optional paper tray (maximum of 1) Paper Output

150 sheets face down

1 sheet face up (straight paper path)

Media Specifications

Media Types & Weights

Media Sizes

Standard / Optional Paper Tray - Plain & recycled paper (between 60 - 105 g/m2) Multi-Purpose Tray - Plain, recycled & bond paper (between 60 - 163 g/m2) Standard / Optional Paper Tray - A4, Letter, B5(ISO/JIS), A5, A5(Long Edge), B6(ISO),

Multi-Purpose Tray - Width: 76.2mm to 215.9mm x Length: 127mm to 355.6mm

Supported Operating Systems

Windows Windows 7º (32 & 64 bit editions), Windows Vista® (32 & 64 bit editions), Windows® XP Professional (32 & 64 bit editions), Windows® XP Home

Edition, Windows® Server 2008R2, Windows® Server 2008 (32 & 64 bit editions), Windows® Server 2003 (32 & 64 bit editions)

Macintosh Mac OS X 10.5.8, 10.6.x, 10.7.x Linux CUPS, LPD/LPRng (x86/x64 environment)

Driver Functions

N-up Printing Poster Printing³ Watermark Printing³

Macro Printing

ID Printing³

Reduce up to 2, 4, 9, 16 or 25 A4 pages into just one A4 page Enlarge 1 A4 page into a poster using 4, 9, 16 or 25 A4 pages Watermark your documents with predefined text or with your own

user-defined messages

Create & embed custom templates, for example a company logo, which

automatically prints on all of your printed documents Add identification to your printed documents (date & time, short custom message or PC username)

Booklet Printing Print documents in A5 booklet format using automatic or manual 2-sided print Quiet Mode Reduces the noise of the machine whilst printing (a small reduction in print

Skip Blank Page³ Ignores any pages blank pages in your documents Print the last document that was sent to the machine

Network Utilities/Protocols

Web Based Management Driver Deployment Wizard BRAdmin Professional Print Log to Network E-mail Notifications

IPv6 Supported Protocols

Web browser based management software A quick & easy way to deploy Brother printer drivers on a networked Windows® PC

For LAN / WAN management (Downloadable from http://solutions.brother.com) Records printing activities from individual users

Automatic alerts sent via e-mail when the device needs attention, e.g. toner low

TCP/IP (IPv4 & IPv6) IPv4 Supported Protocols

ARP, RARP, BOOTP, DHCP, APIPA(Auto IP), WINS/NetBIOS name resolution, DNS Resolver, mDNS, LLMNR responder, LPR/LPD, Custom Raw Port/Port9100, IPP/ IPPS, FTP Server, TELNET Server, HTTP/HTTPS server, TFTP client and server, SMTP Client, SNMPv1/v2c/ v3, ICMP, Web Services (Print), CIFS client, SNTP client NDP. RA. DNS resolver, mDNS, LLMNR responder, LPR/LPD, Custom Raw Port/

Port9100, IPP/IPPS, FTP Server, TELNET Server, HTTP/HTTPS server, TFTP client and server, SMTP Client, SNMPv1/v2c/v3, ICMPv6, Web Services (Print), CIFS Client,

Security Features

Security Protocols Secure Function Lock v2 Secure Printing with SSL

APOP, POP before SMTP, SMTP-AUTH, SSL/TLS (IPPS, HTTPS, SMTP, POP) SNMP v3, Kerberos, 802.1x (EAP-MD5, EAP-FAST, PEAP, EAP-TLS, EAP-TTLS) Restrict print activities to selected users and assign optional page limits IPP based encryption, already widely used in e-commerce to protect financial & sensitive information

IP address based access restriction (IPv4 only)

Supplies / Accessories

In-box Toner High Yield Toner Optional Lower Trav

IP Filter

Approx. 2,000 pages¹ TN-3310 - Approx. 3,000 pages TN-3340 - Approx. 8,000 pages

DR-3325 - Approx. 30,000 pages (one job per page)

LT-5400 - Up to 500 sheets



Weight & Dimensions

Without Carton 371(w) x 384(d) x 245(h) mm / 10.5kg

Environment

Typical Electrical Consumption Power Consumption Sound Pressure Sound Power Toner Save

2 120kWh / week Ready mode: 4.7W. Sleep mode: 0.6W 59dBA active, 54dBA quiet mode, 34dBA ready 6.79BA active, 6.4BA quiet mode, 4.7BA ready Consume less energy when not in use Reduces toner usage



Duty Cycle

Recommended Monthly Print Volume

500 to 3,500 pages

Declared yield value in accordance with ISO/IEC19752, 2Windows® & Mac only, 3Windows® only, 4Connection to wireless Access point/Router required

Contact:



